



TUGE 10

DATASHEET

TUGE 10 is a Class 1 small wind turbine designed and produced in Estonia.

Our competitive advantage is extra safety combined with minimal maintenance and high return on investment.

TUGE ENERGIA OÜ

ANGERJA TEE 42
HÜÜRU KÜLA, 76911
SAUE VALD, ESTONIA

INFO@TUGE.EE
+372 661 11 13

WWW.TUGE.EE



OPERATING PARAMETERS

Maximum power	9.9 kW
Nominal rpm	69
Nominal wind speed	11 m/s

DIMENSIONS

Hub height	18 or 22 m
Rotor diameter	10.2 m
Rotor area	82 m²

ENVIRONMENTAL CONDITIONS

Active wind range	3-25 m/s
Survival wind speed	50 m/s
Operational temperature	-25...+60°C
AWEA rated sound level (Intertek report 103254243CRT-004)	43.7 dB(A)

CONTROL

stall, active inverter, active dump load, tip-brake, active yaw, rotor brake

BLADES

from fiber glass with fail-safe tip-brakes by Olsen Wings

ROTOR BRAKE

fail-safe electromagnetic brake by Intorq

YAW

electric drive with encoder

GENERATOR

permanent magnet synchronous generator

INVERTER

active inverter with TMC3 controller and online SCADA by Orbital

TOWER

tilt-up steel tower in 3 parts and base section

MAINTENANCE

once in every two years due to automatic lubrication system by SKF

CERTIFICATION

IEC 61400 in progress by Intertek

M / S	KW	KWH
5	2.43	27 597
6	4.20	36 261
7	6.37	42 808
8	7.85	47 395
9	8.78	50 423
10	9.36	52 247
11	9.82	52 995